

Polypropylenefilm s2d-PP80-WO

Product:

- Exclusive white drafting film with a fine matt surface for various applications on pen-plotters etc.
- s2d-PP80-WO ensures water resistance, chemical resistance and durability.
- s2d-PP80-WO can be printed by a wide range of printing methods: Flexo, Sheetfed Offset, UV Rotary Letterpress, Silkscreen, etc.
- This grade is mainly designed for Labels and its surface is well suitable for Thermal Transfer Printing.

Physical Properties (measured values):

Thickness		micron	80
Basis Weight		g/m ²	61.2
Opacity		%	91
Gloss		%	10
Brightness		%	96
Tensile Strength	MD	kg/15mm	06
	CD	kg/15mm	18
Tear Strength (Elmendorf)	MD	g	23
	CD	g	13
Clark Stiffness	MD	s-value	19

Production conditioned tolerances may occur Herstellbedingte Toleranzen möglich

Measured at day of material production. Decreasing values are naturally based and they are unavoidable.

Gemessen am Tag der Materialherstellung. Abnehmende Werte haben natürliche Ursachen und sind unvermeidbar.

This document is provided for informational purposes only and is not intended to be a specific agreement. Solutions2day GmbH reserves the right to make changes to the values shown above as required to improve product performance.

Issued: Mai 2020

solutions2day GmbH

Uncontrolled Document